TECHNICAL DATA SHEET PNEUMATIC VIBRATOR

ACBMV B. CASADIO VIBRATION
Z.I. Mi-Plaine
51 Rue Ampère
B.P. 31
69682 CHASSIEU CEDEX (FRANCE)
Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88
Email: vibrateur@orange.fr
Internet: acbmv.com

Roller vibratortype R80 EX

CE EX II 2 G/D c T6 T85°C

Description:
Simply constructed high-frequency roller vibrators, wide range for many applications.

VIBRATING AND PNEUMATIC CARACTERISTICS

	2 Bars/29 PSI	4 Bars/58 PSI	6 Bars/87 PSI
Frequency (RPM)	15500	18500	19000
Force (N)	3000	6090	7450
Force (LBS)	675,68	1371,62	1677,93
Air cons. (l/min)	290	430	570
Air cons. (CF)	10,36	15,36	20,36

Typical applications:
- Emptying of hoppers and chutes
- Screen filters
- Conveying of particulates
- Preventing adhesions in pipelines and silos
- Transport of fine powders
- Compacting of plastic and concrete in troughs

Construction:
- Vibration created by a rotating precision-steel roller
- Shockproof plastic end plates
- Housing with 4 mounting bores, depending on the application

Properties:
- High motive power
- Rated frequency 15500 – 19000 RPM
- Centrifugal force 3000 – 7450 N
- Continuously variable (compressed air)
- Can be used at up to 150°C
- Resistant to extreme environmental conditions



Design:
1 Housing made from extruded aluminium alloy
2 Cast iron strip
3 Steel roller
4 Plastic end plates
5 Vertical air entry
6 Horizontal air entry
7 Air channel
8 Air supply nozzles
9 Outlet openings
10 Outlet diffuser
11 Sound absorber plate
12 Base mounting bores



DIMENSIONAL SPECIFICATIONS



	mm	inch
A	80	3,15
B	43	1,69
C	128	5,04
D	104	4,10
E	16	0,63
F	9	0,35
G	60	60
H	G 1/4”	G 1/4”

	kg	LBS
Vibrator weight	0,95	2,111

This datas and outline drawings of this technical sheet are the property of ACBMV company. Don't reproduce or copy without authorization. This datas and outline drawings are intended to depict overall dimensions and do not necessarily represent the machine exterior. Information contained herein is subject to change without notice.