TECHNICAL DATA SHEET PNEUMATIC VIBRATOR

ACBMV B. CASADIO VIBRATION
Z.I. Mi-Plaine
51 Rue Ampère
B.P. 31
69682 CHASSIEU CEDEX (FRANCE)
Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88
Email: vibrateur@orange.fr
Internet: acbmv.com

Ball vibrator type K13 EX

CE EX II 2 G/D c T6 T85°C

Description:
Ball vibrators, simple and good. Wide range for many applications.

VIBRATING AND PNEUMATIC CARACTERISTICS

	2 Bars/29 PSI	4 Bars/58 PSI	6 Bars/87 PSI
Frequency (RPM)	15000	18500	22500
Force (N)	320	550	870
Force (LBS)	72,07	123,87	195,95
Air cons. (l/min)	94	158	225
Air cons. (CF)	3,36	5,64	8,04

Typical applications:
- Emptying of bunkers
- Screen filters
- Vibrating tables
- Preventing adhesions in pipelines and silos
- Movement of goods

Construction:
- Vibration by means of a ball that is passed through hardened-steel guides.
- Nylon plates on both sides to support the ball and as a protection from dust and water.
- Housing with 4 mounting bores, depending on the application.

Properties:
- Powerful
- Rated frequency 15000 – 22500 RPM
- Centrifugal force 320 – 870 N
- Continuously variable (compressed air)
- Can be used at up to 100°C
- 150 °C on request

Design:
1 Housing made from extruded aluminium alloy
2 Hardened guides made of steel
3 Nylon end plates
4 Hardened ball
5 Air inlet
6 Air outlet
7 Base mounting bores
8 Sideways fitting bores



DIMENSIONAL SPECIFICATIONS



	mm	inch
A	65	2,56
B	24	0,95
C	113	4,45
D	90	3,55
E	16	0,63
F	9	0,35
G	50	50
H	G 1/4”	G 1/4”

	kg	LBS
Vibrator weight	0,26	0,578

This datas and outline drawings of this technical sheet are the property of ACBMV company. Don't reproduce or copy without authorization. This datas and outline drawings are intended to depict overall dimensions and do not necessarily represent the machine exterior. Information contained herein is subject to change without notice.