

ACBMV B. CASADIO VIBRATION

Z.I. Mi-Plaine

51 Rue Ampère

B.P. 31

69682 CHASSIEU CEDEX (FRANCE)

Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88

Email: vibrateur@orange.fr Internet: acbmv.com

TECHNICAL DATA SHEET PNEUMATIC VIBRATOR

Knocker vibrator type FKL50SI EX

CE EX II 2 G/D c T6 T85°C

Description:

For powerful impacts at low operating pressure.

VIBRATING AND PNEUMATIC CARACTERISTICS

	2 Bars/29 PSI	7 Bars/101,5 PSI		
Working/strike (Nm)	5	15		
Impulsion/strike (Ns)	1	3,5		
Air cons. (I/min)	0,1	0,3		
Air cons. (CF)	0,00	0,01		

Typical applications:

Wide range of uses, including in the open air, and in wet or explosion risk areas. For knocking off material adhesions on container walls, such as in silos, hoppers, filter outlets, reactors and pipelines.

Construction:

Compressed air pushes a piston against a spring. When air pressure is rapidly vented, the piston shoots against a baffle plate. Mechanical impact regulation is provided by limiting the piston's stroke by means of an inserted threaded rod. Knocker housing


Properties:

- Wide range of settings for impact power and interval
 Impact force can be set pneumatically and/or by mechanical means
- Flexible range of applications




Design:

Housing made of hard-anodized aluminium alloy Steel piston Baffle plate made of impact-resistant plastic



DIMENSIONAL SPECIFICATIONS



	mm	inch
Α	115	4,53
В	66	2,60
С	90	3,55
D	64	2,52
E	13	0,51
F	194	7,64
G	177	6,97
Н	15	0,59
	L	a IRS

l		kg	LBS
L	Vibrator weight	1,85	4,111