

ACBMV B. CASADIO VIBRATION  
 Z.I. Mi-Plaine  
 51 Rue Ampère  
 B.P. 31  
 69682 CHASSIEU CEDEX (FRANCE)  
 Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88  
 Email: [vibrateur@orange.fr](mailto:vibrateur@orange.fr)  
 Internet: [acbmv.com](http://acbmv.com)

2 POLES - 3600 RPM      ATEX II 2D tD A21 IP 66 ZONE 21-22  
 REF.: 600465C              Dust T°=120°C  
 SIZE: 00

Certifications:



### MECHANICAL AND ELECTRICAL SPECIFICATIONS

Eccentric weight setup (%)	Static moment (kgmm)	Working moment (kgcm)	Centrifugal force (kg)	Centrifugal force (kN)	Estimated bearings life time (hours)
100	9,64	1,93	140	1,37	10987
90	8,68	1,74	126	1,23	15071
80	7,71	1,54	112	1,10	21459
70	6,75	1,35	98	0,96	32032
60	5,78	1,16	84	0,82	50866
50	4,82	0,96	70	0,69	87896
40	3,86	0,77	56	0,55	>100000
30	2,89	0,58	42	0,41	>100000
20	1,93	0,39	28	0,27	>100000
10	0,96	0,19	14	0,14	>100000

Power supply (volts)	460
Phases:	three phases
Frequency (Hz)	60 Hz
Rotation speed (RPM)	3600
Max input power (watt)	180
Max current (amp)	0,3
IS/IR	3

### DIMENSIONAL SPECIFICATIONS (mm)

**Vibrator weight: 5,2 kg**

Continual service ambient temperature: -20°C à +40°C - Tropicalization anti-mold - Mechanical protection: IP66 IK08 according to IEC

Bearing type: BALL

Lubrication "FOR LIFE" with double protection screen

Fixing with 4 screws M8 - 5/16" quality 8.8 with tightening torque (kgm - ft/lb): 2.30 - 16.50

Power supply cable size: 6.5 à 12 mm - Cable entry thread: M20x1,5

Maintenance space: 47 mm



A	211
B	123
C	127
D	30-60
E	85-100
F	24
G	9
N° HOLES	4
H	70
I	47
L	106
M	86
N	106
P	88,5