TECHNICAL DATA SHEET PNEUMATIC VIBRATOR

Turbine vibrator type T65/HP

ACBMV B. CASADIO VIBRATION
Z.I. Mi-Plaine
51 Rue Ampère
B.P. 31
69682 CHASSIEU CEDEX (FRANCE)
Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88
Email: vibrateur@orange.fr
Internet: acbmv.com

Description:
High speed and high working torque for strong vibration at great amplitude. Wide range.

VIBRATING AND PNEUMATIC CARACTERISTICS

	2 Bars/29 PSI	4 Bars/58 PSI	6 Bars/87 PSI
Frequency (RPM)	8500	10500	12000
Force (N)	1300	2050	2600
Force (LBS)	292,79	461,71	585,59
Air cons. (l/min)	108	193	290
Air cons. (CF)	3,86	6,89	10,36

Typical applications:
- Emptying of bunkers
- Screen filters
- Vibrating tables
- Preventing adhesions in pipelines and silos
- Transport of fine powders
- Movement of bulk materials

Construction:
- Vibration with a high eccentric torque, caused by the rotor's unbalance
- Low noise level

Properties:
- Rated frequency 8500 – 12000 RPM
- Centrifugal force 1300 – 2600 N
- Continuously variable (Compressed air)
- Can be used at up to 150°C
- Resistant to extreme environmental conditions

Design:
1 Housing made from extruded aluminium alloy with hard anodization
2 Turbine rotor
3 Aluminium = light
4 Brass = heavy
5 Ball bearing
6 Plastic end plate with screw thread
7 Nylon end plate
8 Speed channels
9 Air supply
10 Air outlet
11 Base mounting bores



DIMENSIONAL SPECIFICATIONS



	mm	inch
A	65	2,56
B	64	2,52
C	113	4,45
D	90	3,55
E	16	0,63
F	9	0,35
G	G 1/4"	G 1/4"
H	G 1/4"	G 1/4"

	kg	LBS
Vibrator weight	0,975	2,167

This datas and outline drawings of this technical sheet are the property of ACBMV company. Don't reproduce or copy without authorization. This datas and outline drawings are intended to depict overall dimensions and do not necessarily represent the machine exterior. Information contained herein is subject to change without notice.