TECHNICAL DATA SHEET PNEUMATIC VIBRATOR

Lubrication free internal piston vibratortype FPLF35L

ACBMV B. CASADIO VIBRATION
Z.I. Mi-Plaine
51 Rue Ampère
B.P. 31
69682 CHASSIEU CEDEX (FRANCE)
Tel.: 04 78 90 87 87 / Fax.: 04 78 90 87 88
Email: vibrateur@orange.fr
Internet: acbmv.com

Description:
Lubrication free pneumatic piston vibrators for a linear vibration with unlimited fine-tuning facilities for amplitude and frequency. Wide range.

VIBRATING AND PNEUMATIC CARACTERISTICS

	2 Bars/29 PSI	4 Bars/58 PSI	6 Bars/87 PSI
Frequency (strike/min)	2400	3100	3600
Force (N)	282	680	1066
Force (LBS)	63,51	153,15	240,09
Air cons. (l/min)	38	89	135
Air cons. (CF)	1,36	3,18	4,82

Typical applications:
- Foodstuffs and pharmaceuticals
- Driving conveyor and discharge chutes
- Loosening or compacting of bulk materials
- Starting up of mechanical processes
- Filling facilities

Construction:
- Lubrication free operation possible.
- Extra hard and corrosion-resistant surface through aluminium oxide-generated by titaniferous electrolyte.
- Ideally suited for foodstuffs, drinks and pharmaceuticals.

Properties:
- Efficient
- Nominal frequency 2400 – 3600 strikes/min
- Centrifugal force 282 – 1066 N
- Frequency and amplitude can be regulated
- Can be used at temperatures up to 150°C
- Resistant to extreme environmental conditions
- Extremely low noise level

Design:
Housing made from hard-anodized aluminium alloy
Piston made from leaded-bronze
Steel spring starting device
Sound-absorbing air outlet system
Hard anodized aluminium base
Threaded insert for mounting purposes

DIMENSIONAL SPECIFICATIONS



	mm	inch
A	136	5,36
B	136	5,36
C	65	2,56
D	M12	M12
E	G 1/4”	G 1/4”
F	G 1/4”	G 1/4”

	kg	LBS
Vibrator weight	1,28	2,844
Housing weight	0,7	1,556
Piston weight	0,58	1,289

This datas and outline drawings of this technical sheet are the property of ACBMV company. Don't reproduce or copy without authorization. This datas and outline drawings are intended to depict overall dimensions and do not necessarily represent the machine exterior. Information contained herein is subject to change without notice.